




HD-PE

PIPE FITTING VALVE

HD-PE 60° Y-TEE

(Fabricated)
for butt welding
molded from PE100

手工對接60° Y型三通
DFP TY5



OD (mm)	H (mm)	L (mm)	SDR27.6 ISO S13.3 PN6		SDR17 ISO S8 PN10		SDR11 ISO S5 PN16	
			Code	S (mm)	Code	S (mm)	Code	S (mm)
63	125	248	31-TY5-27-0063	2.3	31-TY5-17-0063	3.8	31-TY5-11-0063	5.8
90	148	279	31-TY5-27-0090	3.3	31-TY5-17-0090	5.4	31-TY5-11-0090	8.2
110	175	327	31-TY5-27-0110	4.0	31-TY5-17-0110	6.6	31-TY5-11-0110	10.0
125	198	370	31-TY5-27-0125	4.6	31-TY5-17-0125	7.4	31-TY5-11-0125	11.4
140	211	387	31-TY5-27-0140	5.1	31-TY5-17-0140	8.3	31-TY5-11-0140	12.7
160	239	435	31-TY5-27-0160	5.8	31-TY5-17-0160	9.5	31-TY5-11-0160	14.6
180	256	456	31-TY5-27-0180	6.6	31-TY5-17-0180	10.7	31-TY5-11-0180	16.4
200	283	504	31-TY5-27-0200	7.3	31-TY5-17-0200	11.9	31-TY5-11-0200	18.2
225	315	560	31-TY5-27-0225	8.2	31-TY5-17-0225	13.4	31-TY5-11-0225	20.5
250	352	624	31-TY5-27-0250	9.1	31-TY5-17-0250	14.8	31-TY5-11-0250	22.7
280	392	699	31-TY5-27-0280	10.2	31-TY5-17-0280	16.6	31-TY5-11-0280	25.4
315	443	789	31-TY5-27-0315	11.4	31-TY5-17-0315	18.7	31-TY5-11-0315	28.6
355	492	873	31-TY5-27-0355	12.9	31-TY5-17-0355	21.1	31-TY5-11-0355	32.2
400	556	987	31-TY5-27-0400	14.5	31-TY5-17-0400	23.7	31-TY5-11-0400	36.3
450	625	1107	31-TY5-27-0450	16.3	31-TY5-17-0450	26.7	31-TY5-11-0450	40.9
500	693	1228	31-TY5-27-0500	18.1	31-TY5-17-0500	29.7	31-TY5-11-0500	45.4
560	775	1372	31-TY5-27-0560	20.3	31-TY5-17-0560	33.2	31-TY5-11-0560	50.8
630	871	1540	31-TY5-27-0630	22.8	31-TY5-17-0630	37.4	31-TY5-11-0630	57.2
710	980	1733	31-TY5-27-0710	25.7	31-TY5-17-0710	42.1	31-TY5-11-0710	64.5
800	1103	1947	31-TY5-27-0800	29.0	31-TY5-17-0800	47.4	31-TY5-11-0800	72.8
900	1239	2188	31-TY5-27-0900	32.6	31-TY5-17-0900	53.3	31-TY5-11-0900	81.8
1000	1386	2455	31-TY5-27-1000	36.2	31-TY5-17-1000	59.3	-	-
1200	1659	2936	31-TY5-27-1200	43.5	31-TY5-17-1200	67.9	-	-