




HD-PE PIPE FITTING VALVE


HD-PE 90° BEND

for butt welding
molded from PE100

對接90°彎頭
DFP L91



(Ø20~Ø110, 140, 160, 225, 280)




(Ø125, 180, 200, 250, 315)

OD (mm)	H (mm)	L (mm)	SDR27.6 ISO S13.3 PN6		SDR17 ISO S8 PN10		SDR11 ISO S5 PN16	
			Code	S1/S2 (mm)	Code	S1/S2 (mm)	Code	S1/S2 (mm)
20	15.5	37.0	-	-	-	-	31-L93-17-0020	2.0
25	15.5	42.5	-	-	-	-	31-L93-17-0025	2.3
32	17.5	48.0	-	-	-	-	31-L93-17-0032	2.9
40	12.0	49.0	-	-	-	-	31-L93-17-0040	3.7
50	14.0	56.0	-	-	31-L93-17-0050	3.0	31-L93-17-0050	4.6
63	18.0	72.6	31-L93-27-0063	2.3	31-L93-17-0063	3.8	31-L93-17-0063	5.8
75	15.0	80.5	31-L93-27-0075	2.7	31-L93-17-0075	4.5	31-L93-17-0075	6.8
90	38.5	111.0	31-L93-27-0090	3.3	31-L93-17-0090	5.4	31-L93-17-0090	8.2
110	49.0	130.0	31-L93-27-0110	4.0	31-L93-17-0110	6.6	31-L93-17-0110	10.0
125	102.0	164.5	31-L93-27-0125	4.6	31-L93-17-0125	7.4	31-L93-17-0125	11.4
140	90.0	185.0	31-L93-27-0140	5.1	31-L93-17-0140	8.3	31-L93-17-0140	12.7
160	92.0	190.0	31-L93-27-0160	5.8	31-L93-17-0160	9.5	31-L93-17-0160	14.6
180	136.5	226.5	31-L93-27-0180	6.6	31-L93-17-0180	10.7	31-L93-17-0180	16.4
200	119.5	219.5	31-L93-27-0200	7.3	31-L93-17-0200	11.9	31-L93-17-0200	18.2
225	100.0	240.0	31-L93-27-0225	8.2	31-L93-17-0225	13.4	31-L93-17-0225	20.5
250	148.0	402.5	31-L93-27-0250	9.1	31-L93-17-0250	14.8	31-L93-17-0250	22.7
280	196.0	336.0	31-L93-27-0280	10.2	31-L93-17-0280	16.6	31-L93-17-0280	25.4
315	212.0	365.0	31-L93-27-0315	11.4	31-L93-17-0315	18.7	31-L93-17-0315	28.6

HD-PE 90° ELBOW

(Fabricated)
for butt welding
molded from PE100

手工90°彎頭
DFP L94



OD (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	SDR27.6 ISO S13.3 PN6		SDR17 ISO S8 PN10		SDR11 ISO S5 PN16	
					Code	S1/S2 (mm)	Code	S1/S2 (mm)	Code	S1/S2 (mm)
355	185	280	375	615	31-L94-27-0355	12.9	31-L94-17-0355	21.1	31-L94-11-0355	32.2
400	210	317	424	697	31-L94-27-0400	14.5	31-L94-17-0400	23.7	31-L94-11-0400	36.3
450	235	356	476	781	31-L94-27-0450	16.3	31-L94-17-0450	26.7	31-L94-11-0450	40.9
500	260	394	528	865	31-L94-27-0500	18.1	31-L94-17-0500	29.7	31-L94-11-0500	45.4
560	290	440	589	966	31-L94-27-0560	20.3	31-L94-17-0560	33.2	31-L94-11-0560	50.8
630	325	494	663	1084	31-L94-27-0630	22.8	31-L94-17-0630	37.4	31-L94-11-0630	57.2
710	365	555	745	1219	31-L94-27-0710	25.7	31-L94-17-0710	42.1	31-L94-11-0710	64.5
800	410	625	838	1370	31-L94-27-0800	29.0	31-L94-17-0800	47.4	31-L94-11-0800	72.8
900	460	701	942	1539	31-L94-27-0900	32.6	31-L94-17-0900	53.3	31-L94-11-0900	81.8
1000	520	788	1058	1731	31-L94-27-1000	36.2	31-L94-17-1000	59.3	-	-
1200	620	942	1263	2067	31-L94-27-1200	43.5	31-L94-17-1200	67.9	-	-