




PP-H/PP-H(FRP COATED) PIPE FITTING VALVE

PP-H 45° ELBOW

for butt welding
molded from PP-H

對接45°彎頭
DFP L45




OD (mm)	H (mm)	L (mm)	SDR17.6 ISO S13.3 PN6		SDR11 ISO S5 PN10		SDR7.4 ISO S3.2 PN16	
			Code	S (mm)	Code	S (mm)	Code	S (mm)
20	28	32.0	-	-	21-L45-11-0020	2.5	21-L45-07-0020	2.8
25	29	34.0	-	-	21-L45-11-0025	2.7	21-L45-07-0025	3.5
32	30	36.0	-	-	21-L45-11-0032	3.0	21-L45-07-0032	4.5
40	31	39.0	-	-	21-L45-11-0040	3.7	21-L45-07-0040	5.6
50	32	42.0	21-L45-17-0050	2.9	21-L45-11-0050	4.6	21-L45-07-0050	6.9
63	34	47.0	21-L45-17-0063	3.6	21-L45-11-0063	5.8	21-L45-07-0063	8.7
75	34	49.0	21-L45-17-0075	4.3	21-L45-11-0075	6.9	21-L45-07-0075	10.4
90	36	55.0	21-L45-17-0090	5.1	21-L45-11-0090	8.2	21-L45-07-0090	12.5
110	45	68.0	21-L45-17-0110	6.3	21-L45-11-0110	10.0	21-L45-07-0110	15.2
125	50	81.0	21-L45-17-0125	7.1	21-L45-11-0125	11.4	21-L45-07-0125	--
140	55	91.5	21-L45-17-0140	8.0	21-L45-11-0140	12.8	21-L45-07-0140	--
160	60	94.0	21-L45-17-0160	9.1	21-L45-11-0160	14.6	21-L45-07-0160	--
180	65	110.0	21-L45-17-0180	10.2	21-L45-11-0180	16.4	21-L45-07-0180	--
200	70	120.0	21-L45-17-0200	11.4	21-L45-11-0200	18.2	21-L45-07-0200	--
225	80	127.0	21-L45-17-0225	12.8	21-L45-11-0225	20.5	21-L45-07-0225	--
250	90	150.0	21-L45-17-0250	14.2	21-L45-11-0250	22.8	21-L45-07-0250	--
280	100	170.0	21-L45-17-0280	15.9	21-L45-11-0280	25.5	21-L45-07-0280	--
315	110	184.0	21-L45-17-0315	17.9	21-L45-11-0315	28.7	21-L45-07-0315	--

PP-H 45° ELBOW

(Fabricated)
for butt welding
molded from PP-H

手工對接45°彎頭
DFP L47



OD (mm)	H (mm)	H ₁ (mm)	H ₂ (mm)	L (mm)	SDR17.6 ISO S8.3 PN6		SDR11 ISO S5 PN10	
					Code	S (mm)	Code	S (mm)
355	185	256	326	359	21-L47-17-0355	20.1	21-L47-11-0355	32.3
400	210	289	370	407	21-L47-17-0400	22.7	21-L47-11-0400	36.4
450	235	325	413	455	21-L47-17-0450	25.5	21-L47-11-0450	41.0
500	260	360	458	504	21-L47-17-0500	28.3	21-L47-11-0500	45.5
560	290	402	512	563	21-L47-17-0560	31.7	21-L47-11-0560	50.9
630	325	450	576	631	21-L47-17-0630	35.7	21-L47-11-0630	57.2
710	365	506	648	710	21-L47-17-0710	40.2	21-L47-11-0710	64.5
800	410	569	729	798	21-L47-17-0800	45.5	21-L47-11-0800	72.7
900	460	639	818	895	21-L47-17-0900	51.2	21-L47-11-0900	81.8
1000	520	719	918	1009	21-L47-17-1000	56.8	21-L47-11-1000	90.9
1200	620	858	1099	1204	21-L47-17-1200	68.1	21-L47-11-1200	109.0