




# PP-H/PP-H(FRP COATED) PIPE FITTING VALVE

## PP-H REDUCER

concentric, elongated  
for butt welding  
molded from PP-H

對接大小頭  
DFP RC1




OD <sub>1</sub> /OD <sub>2</sub> (mm)	L (mm)	L <sub>1</sub> (mm)	L <sub>2</sub> (mm)	SDR17.6 ISO S8.3 PN6		SDR11 ISO S5 PN10	
				Code	S <sub>1</sub> /S <sub>2</sub> (mm)	Code	S <sub>1</sub> /S <sub>2</sub> (mm)
25-20	50	20	20	-	-	21-RC1-11-025020	2.7/2.5
32-20	50	20	20	-	-	21-RC1-11-032020	3.0/2.5
32-25	50	20	20	-	-	21-RC1-11-032025	3.0/2.7
40-20	55	20	20	-	-	21-RC1-11-040020	3.7/2.5
40-25	55	20	20	-	-	21-RC1-11-040025	3.7/2.7
40-32	55	20	20	-	-	21-RC1-11-040032	3.7/3.0
50-20	60	24	20	-	-	21-RC1-11-050020	4.6/2.5
50-25	60	24	20	-	-	21-RC1-11-050025	4.6/2.7
50-32	60	24	20	-	-	21-RC1-11-050032	4.6/3.0
50-40	60	24	20	-	-	21-RC1-11-050040	4.6/3.7
63-25	65	25	20	-	-	21-RC1-11-063025	5.8/2.7
63-32	65	25	22	-	-	21-RC1-11-063032	5.8/3.0
63-40	65	25	22	-	-	21-RC1-11-063040	5.8/3.7
63-50	65	25	22	21-RC1-17-063050	3.6/2.9	21-RC1-11-063050	5.8/4.6
75-40	68	25	24	21-RC1-17-075040	4.3/2.3	21-RC1-11-075040	6.9/3.7
75-50	68	25	24	21-RC1-17-075050	4.3/2.9	21-RC1-11-075050	6.9/4.6
75-63	68	25	24	21-RC1-17-075063	4.3/3.6	21-RC1-11-075063	6.9/5.8
90-50	75	30	26	21-RC1-17-090050	5.1/2.9	21-RC1-11-090050	8.2/4.6
90-63	75	30	26	21-RC1-17-090063	5.1/3.6	21-RC1-11-090063	8.2/5.8
90-75	75	30	26	21-RC1-17-090075	5.1/4.3	21-RC1-11-090075	8.2/6.9
110-63	90	35	30	21-RC1-17-110063	6.3/3.6	21-RC1-11-110063	10.0/5.8
110-75	90	35	30	21-RC1-17-110075	6.3/4.3	21-RC1-11-110075	10.0/6.9
110-90	90	35	30	21-RC1-17-110090	6.3/5.1	21-RC1-11-110090	10.0/8.2
125-110	100	40	35	21-RC1-17-120110	7.1/6.3	21-RC1-11-120110	11.4/10.0
140-125	110	45	40	21-RC1-17-140125	8.0/7.1	21-RC1-11-140125	12.8/11.4
160-110	130	60	40	21-RC1-17-160110	9.1/6.3	21-RC1-11-160110	14.6/10.0
160-140	130	60	40	21-RC1-17-160140	9.1/8.0	21-RC1-11-160140	14.6/12.8
180-160	130	60	40	21-RC1-17-180160	10.2/9.1	21-RC1-11-180160	16.4/14.6
200-160	140	60	40	21-RC1-17-200160	11.4/9.1	21-RC1-11-200160	18.2/14.6
225-160	150	60	40	21-RC1-17-225160	12.8/9.1	21-RC1-11-225160	20.5/14.6
225-200	150	60	50	21-RC1-17-225200	12.8/11.4	21-RC1-11-225200	20.5/18.2
250-225	170	70	60	21-RC1-17-250220	14.2/12.8	21-RC1-11-250220	22.8/20.5
280-250	180	80	60	21-RC1-17-280250	15.9/14.2	21-RC1-11-280250	25.5/22.8
315-280	220	90	80	21-RC1-17-315280	17.9/15.9	21-RC1-11-315280	28.7/25.5



# PP-H/PP-H(FRP COATED) PIPE FITTING VALVE

## PP-H REDUCER

(Fabricated)  
concentric, elongated  
for butt welding  
molded from PP-H  
手工對接大小頭  
DFP RC1



OD <sub>1</sub> /OD <sub>2</sub> (mm)	L (mm)	L <sub>1</sub> (mm)	L <sub>2</sub> (mm)	SDR17.6 ISO S8.3 PN6		SDR11 ISO S5 PN10	
				Code	S <sub>1</sub> /S <sub>2</sub> (mm)	Code	S <sub>1</sub> /S <sub>2</sub> (mm)
355-180	318	180	110	21-RC1-17-355180	20.1/10.2	21-RC1-11-355180	32.3/16.4
355-200	328	180	120	21-RC1-17-355200	20.1/11.4	21-RC1-11-355200	32.3/18.2
355-225	328	180	120	21-RC1-17-355225	20.1/12.8	21-RC1-11-355225	32.3/20.5
355-250	338	180	130	21-RC1-17-355250	20.1/14.2	21-RC1-11-355250	32.3/22.8
355-280	358	180	150	21-RC1-17-355280	20.1/15.9	21-RC1-11-355280	32.3/25.5
355-315	368	180	160	21-RC1-17-355315	20.1/17.9	21-RC1-11-355315	32.3/28.7
400-200	358	210	120	21-RC1-17-400200	22.7/11.4	21-RC1-11-400200	36.4/18.2
400-225	358	210	120	21-RC1-17-400225	22.7/12.8	21-RC1-11-400225	36.4/20.5
400-250	368	210	130	21-RC1-17-400250	22.7/14.2	21-RC1-11-400250	36.4/22.8
400-280	388	210	150	21-RC1-17-400280	22.7/15.9	21-RC1-11-400280	36.4/25.5
400-315	398	210	160	21-RC1-17-400315	22.7/17.9	21-RC1-11-400315	36.4/28.7
400-355	418	210	180	21-RC1-17-400355	22.7/20.1	21-RC1-11-400355	36.4/32.3
450-225	398	250	120	21-RC1-17-450225	25.5/12.8	21-RC1-11-450225	41.0/20.5
450-250	408	250	130	21-RC1-17-450250	25.5/14.2	21-RC1-11-450250	41.0/22.8
450-280	428	250	150	21-RC1-17-450280	25.5/15.9	21-RC1-11-450280	41.0/25.5
450-315	438	250	160	21-RC1-17-450315	25.5/17.9	21-RC1-11-450315	41.0/28.7
450-355	458	250	180	21-RC1-17-450355	25.5/20.1	21-RC1-11-450355	41.0/32.3
450-400	488	250	210	21-RC1-17-450400	25.5/22.7	21-RC1-11-450400	41.0/36.4
500-250	438	280	130	21-RC1-17-500250	28.3/14.2	21-RC1-11-500250	45.5/22.8
500-280	458	280	150	21-RC1-17-500280	28.3/15.9	21-RC1-11-500280	45.5/25.5
500-315	468	280	160	21-RC1-17-500315	28.3/17.9	21-RC1-11-500315	45.5/28.7
500-355	488	280	180	21-RC1-17-500355	28.3/20.1	21-RC1-11-500355	45.5/32.3
500-400	518	280	210	21-RC1-17-500400	28.3/22.7	21-RC1-11-500400	45.5/36.4
500-450	558	280	250	21-RC1-17-500450	28.3/25.5	21-RC1-11-500450	45.5/41.0
560-280	478	300	150	21-RC1-17-560280	31.7/15.9	21-RC1-11-560280	50.9/25.5
560-315	488	300	160	21-RC1-17-560315	31.7/17.9	21-RC1-11-560315	50.9/28.7
560-355	508	300	180	21-RC1-17-560355	31.7/20.1	21-RC1-11-560355	50.9/32.3
560-400	538	300	210	21-RC1-17-560400	31.7/22.7	21-RC1-11-560400	50.9/36.4
560-450	578	300	250	21-RC1-17-560450	31.7/25.5	21-RC1-11-560450	50.9/41.0
560-500	608	300	280	21-RC1-17-560500	31.7/28.3	21-RC1-11-560500	50.9/45.5
630-315	538	350	160	21-RC1-17-630315	35.7/17.9	21-RC1-11-630315	57.2/28.7
630-355	558	350	180	21-RC1-17-630355	35.7/20.1	21-RC1-11-630355	57.2/32.3
630-400	588	350	210	21-RC1-17-630400	35.7/22.7	21-RC1-11-630400	57.2/36.4
630-450	628	350	250	21-RC1-17-630450	35.7/25.5	21-RC1-11-630450	57.2/41.0
630-500	658	350	280	21-RC1-17-630500	35.7/28.3	21-RC1-11-630500	57.2/45.5
630-560	678	350	300	21-RC1-17-630560	35.7/31.7	21-RC1-11-630560	57.2/50.9




# PP-H/PP-H(FRP COATED) PIPE FITTING VALVE

## PP-H REDUCER

(Fabricated)  
concentric, elongated  
for butt welding  
molded from PP-H

手工對接大小頭

DFP RC1



OD <sub>1</sub> /OD <sub>2</sub> (mm)	L (mm)	L <sub>1</sub> (mm)	L <sub>2</sub> (mm)	SDR17.6 ISO S8.3 PN6		SDR11 ISO S5 PN10	
				Code	S <sub>1</sub> /S <sub>2</sub> (mm)	Code	S <sub>1</sub> /S <sub>2</sub> (mm)
710-355	608	400	180	21-RC1-17-710355	40.2/20.1	21-RC1-11-710355	64.5/32.3
710-400	638	400	210	21-RC1-17-710400	40.2/22.7	21-RC1-11-710400	64.5/36.4
710-450	678	400	250	21-RC1-17-710450	40.2/25.5	21-RC1-11-710450	64.5/41.0
710-500	708	400	280	21-RC1-17-710500	40.2/28.3	21-RC1-11-710500	64.5/45.5
710-560	728	400	300	21-RC1-17-710560	40.2/31.7	21-RC1-11-710560	64.5/50.9
710-630	778	400	350	21-RC1-17-710630	40.2/35.7	21-RC1-11-710630	64.5/57.2
800-400	688	450	210	21-RC1-17-800400	45.5/22.7	21-RC1-11-800400	72.7/36.4
800-450	728	450	250	21-RC1-17-800450	45.5/25.5	21-RC1-11-800450	72.7/41.0
800-500	758	450	280	21-RC1-17-800500	45.5/28.3	21-RC1-11-800500	72.7/45.5
800-560	778	450	300	21-RC1-17-800560	45.5/31.7	21-RC1-11-800560	72.7/50.9
800-630	828	450	350	21-RC1-17-800630	45.5/35.7	21-RC1-11-800630	72.7/57.2
800-710	878	450	400	21-RC1-17-800710	45.5/40.2	21-RC1-11-800710	72.7/64.5
900-450	778	500	250	21-RC1-17-900450	51.2/25.5	21-RC1-11-900450	81.8/41.0
900-500	808	500	280	21-RC1-17-900500	51.2/28.3	21-RC1-11-900500	81.8/45.5
900-560	828	500	300	21-RC1-17-900560	51.2/31.7	21-RC1-11-900560	81.8/50.9
900-630	878	500	350	21-RC1-17-900630	51.2/35.7	21-RC1-11-900630	81.8/57.2
900-710	928	500	400	21-RC1-17-900710	51.2/40.2	21-RC1-11-900710	81.8/64.5
900-800	978	500	450	21-RC1-17-900800	51.2/45.5	21-RC1-11-900800	81.8/72.7
1000-500	858	550	280	21-RC1-17-100500	56.8/28.3	21-RC1-11-100500	90.9/45.5
1000-560	878	550	300	21-RC1-17-100560	56.8/31.7	21-RC1-11-100560	90.9/50.9
1000-630	928	550	350	21-RC1-17-100630	56.8/35.7	21-RC1-11-100630	90.9/57.2
1000-710	978	550	400	21-RC1-17-100710	56.8/40.2	21-RC1-11-100710	90.9/64.5
1000-800	1028	550	450	21-RC1-17-100800	56.8/45.5	21-RC1-11-100800	90.9/72.7
1000-900	1078	550	500	21-RC1-17-100900	56.8/51.2	21-RC1-11-100900	90.9/81.8
1200-560	928	600	300	21-RC1-17-120560	68.1/31.7	21-RC1-11-120560	109.0/50.9
1200-630	978	600	350	21-RC1-17-120630	68.1/35.7	21-RC1-11-120630	109.0/57.2
1200-710	1028	600	400	21-RC1-17-120710	68.1/40.2	21-RC1-11-120710	109.0/64.5
1200-800	1078	600	450	21-RC1-17-120800	68.1/45.5	21-RC1-11-120800	109.0/72.7
1200-900	1128	600	500	21-RC1-17-120900	68.1/51.2	21-RC1-11-120900	109.0/81.8
1200-1000	1178	600	550	21-RC1-17-120100	68.1/56.8	21-RC1-11-120100	109.0/90.9