




HD-PE

PIPE FITTING VALVE


HD-PE 90° BEND

Elongated
for butt welding
molded from PE100

對接長型90°彎頭
DFP L93



(Ø20~Ø110, 140, 160, 225, 280)



(Ø125, 180, 200, 250, 315)

OD (mm)	H (mm)	L (mm)	SDR27.6 ISO S13.3 PN6		SDR17 ISO S8 PN10		SDR11 ISO S5 PN16	
			Code	S (mm)	Code	S (mm)	Code	S (mm)
20	41.0	64.0	-	-	-	-	31-L93-17-0020	2.0
25	41.0	69.0	-	-	-	-	31-L93-17-0025	2.3
32	46.0	77.0	-	-	-	-	31-L93-17-0032	2.9
40	51.0	89.0	-	-	-	-	31-L93-17-0040	3.7
50	57.0	99.0	-	-	31-L93-17-0050	3.0	31-L93-17-0050	4.6
63	65.0	115.0	31-L93-27-0063	2.3	31-L93-17-0063	3.8	31-L93-17-0063	5.8
75	45.0	125.0	31-L93-27-0075	2.7	31-L93-17-0075	4.5	31-L93-17-0075	6.8
90	84.0	158.5	31-L93-27-0090	3.3	31-L93-17-0090	5.4	31-L93-17-0090	8.2
110	91.0	175.5	31-L93-27-0110	4.0	31-L93-17-0110	6.6	31-L93-17-0110	10.0
125	102.0	164.5	31-L93-27-0125	4.6	31-L93-17-0125	7.4	31-L93-17-0125	11.4
140	90.0	185.0	31-L93-27-0140	5.1	31-L93-17-0140	8.3	31-L93-17-0140	12.7
160	92.0	190.0	31-L93-27-0160	5.8	31-L93-17-0160	9.5	31-L93-17-0160	14.6
180	136.5	226.5	31-L93-27-0180	6.6	31-L93-17-0180	10.7	31-L93-17-0180	16.4
200	119.5	219.5	31-L93-27-0200	7.3	31-L93-17-0200	11.9	31-L93-17-0200	18.2
225	100.0	240.0	31-L93-27-0225	8.2	31-L93-17-0225	13.4	31-L93-17-0225	20.5
250	148.0	402.5	31-L93-27-0250	9.1	31-L93-17-0250	14.8	31-L93-17-0250	22.7
280	196.0	336.0	31-L93-27-0280	10.2	31-L93-17-0280	16.6	31-L93-17-0280	25.4
315	212.0	365.0	31-L93-27-0315	11.4	31-L93-17-0315	18.7	31-L93-17-0315	28.6