




HD-PE

PIPE FITTING VALVE

HD-PE 45° ELBOW

for butt welding
molded from PE100

對接45°彎頭
DFP L45




OD (mm)	H (mm)	L (mm)	SDR27.6 ISO S13.3 PN6		SDR17 ISO S8 PN10		SDR11 ISO S5 PN16	
			Code	S (mm)	Code	S (mm)	Code	S (mm)
20	41.5	54.0	-	-	-	-	31-L45-11-0020	2.0
25	41.0	57.0	-	-	-	-	31-L45-11-0025	2.3
32	46.0	61.0	-	-	-	-	31-L45-11-0032	2.9
40	51.0	68.5	-	-	-	-	31-L45-11-0040	3.7
50	57.0	73.5	-	-	31-L45-17-0050	3.0	31-L45-11-0050	4.6
63	65.0	95.0	31-L45-27-0063	2.3	31-L45-17-0063	3.8	31-L45-11-0063	5.8
75	70.0	90.0	31-L45-27-0075	2.7	31-L45-17-0075	4.5	31-L45-11-0075	6.8
90	79.0	101.0	31-L45-27-0090	3.3	31-L45-17-0090	5.4	31-L45-11-0090	8.2
110	82.0	108.0	31-L45-27-0110	4.0	31-L45-17-0110	6.6	31-L45-11-0110	10.0
125	99.5	130.5	31-L45-27-0125	4.6	31-L45-17-0125	7.4	31-L45-11-0125	11.4
140	108.5	145.0	31-L45-27-0140	5.1	31-L45-17-0140	8.3	31-L45-11-0140	12.7
160	116.5	156.5	31-L45-27-0160	5.8	31-L45-17-0160	9.5	31-L45-11-0160	14.6
180	133.5	178.5	31-L45-27-0180	6.6	31-L45-17-0180	10.7	31-L45-11-0180	16.4
200	122.0	172.0	31-L45-27-0200	7.3	31-L45-17-0200	11.9	31-L45-11-0200	18.2
225	138.0	185.0	31-L45-27-0225	8.2	31-L45-17-0225	13.4	31-L45-11-0225	20.5
250	157.0	217.0	31-L45-27-0250	9.1	31-L45-17-0250	14.8	31-L45-11-0250	22.7
280	167.0	238.0	31-L45-27-0280	10.2	31-L45-17-0280	16.6	31-L45-11-0280	25.4
315	177.0	251.0	31-L45-27-0315	11.4	31-L45-17-0315	18.7	31-L45-11-0315	28.6

HD-PE 45° ELBOW

(Fabricated)
for butt welding
molded from PE100

手工對接45°彎頭
DFP L47



OD (mm)	H (mm)	H ₁ (mm)	H ₂ (mm)	L (mm)	SDR27.6 ISO S13.3 PN6		SDR17 ISO S8 PN10		SDR11 ISO S5 PN16	
					Code	S (mm)	Code	S (mm)	Code	S (mm)
355	185	256	326	359	31-L47-27-0355	12.9	31-L47-17-0355	21.1	31-L47-11-0355	32.2
400	210	289	370	407	31-L47-27-0400	14.5	31-L47-17-0400	23.7	31-L47-11-0400	36.3
450	235	325	413	455	31-L47-27-0450	16.3	31-L47-17-0450	26.7	31-L47-11-0450	40.9
500	260	360	458	504	31-L47-27-0500	18.1	31-L47-17-0500	29.7	31-L47-11-0500	45.4
560	290	402	512	563	31-L47-27-0560	20.3	31-L47-17-0560	33.2	31-L47-11-0560	50.8
630	325	450	576	631	31-L47-27-0630	22.8	31-L47-17-0630	37.4	31-L47-11-0630	57.2
710	365	506	648	710	31-L47-27-0710	25.7	31-L47-17-0710	42.1	31-L47-11-0710	64.5
800	410	569	729	798	31-L47-27-0800	29.0	31-L47-17-0800	47.4	31-L47-11-0800	72.8
900	460	639	818	895	31-L47-27-0900	32.6	31-L47-17-0900	53.3	31-L47-11-0900	81.8
1000	520	719	918	1009	31-L47-27-1000	36.2	31-L47-17-1000	59.3	-	-
1200	620	858	1099	1204	31-L47-27-1200	43.5	31-L47-17-1200	67.9	-	-