




HD-PE

PIPE FITTING VALVE

HD-PE REDUCED Y-TEE

for butt welding
molded from PE100

對接異徑Y型三通
DFP TY1



OD ₁ /OD ₂ (mm)	H (mm)	L (mm)	P ₁ (mm)	P ₂ (mm)	SDR17.6 ISO S8.3 PN6				Code
					T ₁ (mm)	T ₂ (mm)	T ₃ (mm)	T ₄ (mm)	
63-63	150	253	31	31	3.6	7.8	3.6	7.8	31-TY1-17-063063
90-63	153.53	242	53	31	5.1	11.1	3.6	7.8	31-TY1-17-090063
90-90	214	348	53	53	5.1	11.1	5.1	11.1	31-TY1-17-090090
110-63	172.50	273	65	31	6.3	13.1	3.6	7.8	31-TY1-17-110063
110-110	245	414	65	65	6.3	13.1	6.3	13.1	31-TY1-17-110110
160-110	265.05	374	84	65	9.1	15.8	6.3	13.0	31-TY1-17-160110
160-160	330	530	84	84	9.1	15.8	9.1	15.8	31-TY1-17-160160


OD ₁ /OD ₂ (mm)	H (mm)	L (mm)	P ₁ (mm)	P ₂ (mm)	SDR11 ISO S5 PN10				Code
					T ₁ (mm)	T ₂ (mm)	T ₃ (mm)	T ₄ (mm)	
63-63	150	253	31	31	6.0	10.0	6.0	10.0	31-TY1-11-063063
90-63	153.53	242	53	31	8.2	14.2	6.0	10.0	31-TY1-11-090063
90-90	214	348	53	53	8.5	14.2	8.5	14.2	31-TY1-11-090090
110-63	172.50	273	65	31	10.0	16.8	6.0	10.0	31-TY1-11-110063
110-90	207.35	316.25	65	53	10.0	16.8	8.5	14.2	31-TY1-11-110090
110-110	245	414	65	65	10.0	16.8	10.0	16.8	31-TY1-11-110110
160-90	248.04	356.50	84	53	14.6	21.3	8.3	14.2	31-TY1-11-160090
160-110	265.05	374	84	65	14.6	21.3	10.4	16.7	31-TY1-11-160110
160-160	330	530	84	84	14.6	21.3	14.6	21.3	31-TY1-17-160160

HD-PE REDUCED 45° Y-TEE

(Fabricated)

with reduced branch
for butt welding
molded from PE100

手工對接異徑45°Y型三通
DFP TY6



OD ₁ /OD ₂ (mm)	H (mm)	L (mm)	SDR27.6 ISO S13.3 PN6		SDR17 ISO S8 PN10		SDR11 ISO S5 PN16	
			Code	S ₁ /S ₂ (mm)	Code	S ₁ /S ₂ (mm)	Code	S ₁ /S ₂ (mm)
110-32	174	262	-	-	31-TY6-17-110032	6.6/2.0	31-TY6-11-110032	10.0/2.9
110-40	178	273	-	-	31-TY6-17-110040	6.6/2.4	31-TY6-11-110040	10.0/3.7
110-50	183	287	-	-	31-TY6-17-110050	6.6/3.0	31-TY6-11-110050	10.0/4.6
110-75	195	323	31-TY6-27-110075	4.0/2.7	31-TY6-17-110075	6.6/4.5	31-TY6-11-110075	10.0/6.8
125-40	198	300	-	-	31-TY6-17-125040	7.4/2.4	31-TY6-11-125040	11.4/3.7
125-50	203	314	-	-	31-TY6-17-125050	7.4/3.0	31-TY6-11-125050	11.4/4.6
125-63	220	333	31-TY6-27-125063	4.6/2.3	31-TY6-17-125063	7.4/3.8	31-TY6-11-125063	11.4/5.8
125-75	216	350	31-TY6-27-125075	4.6/2.7	31-TY6-17-125075	7.4/4.5	31-TY6-11-125075	11.4/6.8
125-90	223	371	31-TY6-27-125090	4.6/3.3	31-TY6-17-125090	7.4/5.4	31-TY6-11-125090	11.4/8.2
125-110	233	399	31-TY6-27-125110	4.6/4.0	31-TY6-17-125110	7.4/6.6	31-TY6-11-125110	11.4/10.0