




# PVDF/PVDF(FRP COATED)

## PIPE FITTING VALVE

### PVDF BEND 90°

for butt welding  
Tekelding  
molded from PP-H

對接90°彎頭  
DFP L91




OD (mm)	H (mm)	L (mm)	SDR33 ISO S16 PN10		SDR 21 ISO S10 PN16	
			Code	S (mm)	Code	S (mm)
20	25	45.0	-	-	51-L91-21-0020	1.9
25	26	51.0	-	-	51-L91-21-0025	1.9
32	26	58.0	-	-	51-L91-21-0032	2.4
40	28	68.0	-	-	51-L91-21-0040	2.4
50	28	78.0	-	-	51-L91-21-0050	3.0
63	28	91.0	51-L91-33-0063	2.0	51-L91-21-0063	3.0
75	28	103.0	51-L91-33-0075	2.3	51-L91-21-0075	3.6
90	28	118.0	51-L91-33-0090	2.8	51-L91-21-0090	4.3
110	28	138.0	51-L91-33-0110	3.4	51-L91-21-0110	5.3
125	35	97.5	51-L91-33-0125	3.9	51-L91-21-0125	6.0
140	35	130.0	51-L91-33-0140	4.3	51-L91-21-0140	6.7
160	35	133.0	51-L91-33-0160	4.9	51-L91-21-0160	7.7
180	46	136.0	51-L91-33-0180	5.5	51-L91-21-0180	8.6
200	38	138.0	51-L91-33-0200	6.2	51-L91-21-0200	9.6
225	40	180.0	51-L91-33-0225	6.9	51-L91-21-0225	10.8
250	45	299.5	51-L91-33-0250	7.7	51-L91-21-0250	11.9
280	90	230.0	51-L91-33-0280	8.6	51-L91-21-0280	13.4
315	178	340	51-L91-33-0315	9.7	51-L91-21-0315	15.0

### PVDF ELBOW 90°

molded from PVDF  
(Fabricated)  
for butt welding

手工對接90°彎頭  
DFP L94



OD (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	SDR33 ISO S16 PN10		SDR21 ISO S10 PN16	
					Code	S (mm)	Code	S (mm)
355	160	255	350	556	51-L94-33-0315	10.9	-	-
400	180	287	394	626	51-L94-33-0400	12.3	-	-
450	200	321	441	698	51-L94-33-0450	13.7	-	-
500	220	354	488	771	51-L94-33-0500	15.2	-	-
560	240	390	539	848	51-L94-33-0560	17.0	-	-
630	250	419	588	907	51-L94-33-0630	19.1	-	-

手工製品(Fabricated)