




# PVDF/PVDF(FRP COATED)

## PIPE FITTING VALVE

### PVDF 45° ELBOW

for butt welding  
molded from PVDF

對接45°彎頭  
DFP L45




OD (mm)	H (mm)	L (mm)	SDR33 ISO S16 PN10		SDR21 ISO S10 PN16	
			Code	S (mm)	Code	S (mm)
20	28	32.0	-	-	51-L45-21-0020	1.9
25	29	34.0	-	-	51-L45-21-0025	1.9
32	30	36.0	-	-	51-L45-21-0032	2.4
40	31	39.0	-	-	51-L45-21-0040	2.4
50	32	42.0	-	-	51-L45-21-0050	3.0
63	34	47.0	51-L45-33-0063	2.0	51-L45-21-0063	3.0
75	34	49.0	51-L45-33-0075	2.3	51-L45-21-0075	3.6
90	36	55.0	51-L45-33-0090	2.8	51-L45-21-0090	4.3
110	45	68.0	51-L45-33-0110	3.4	51-L45-21-0110	5.3
125	50	81.0	51-L45-33-0125	3.9	51-L45-21-0125	6.0
140	55	91.5	51-L45-33-0140	4.3	51-L45-21-0140	6.7
160	60	94.0	51-L45-33-0160	4.9	51-L45-21-0160	7.7
180	65	110.0	51-L45-33-0180	5.5	51-L45-21-0180	8.6
200	70	120.0	51-L45-33-0200	6.2	51-L45-21-0200	9.6
225	80	127.0	51-L45-33-0225	6.9	51-L45-21-0225	10.8
250	90	150.0	51-L45-33-0250	7.7	51-L45-21-0250	11.9
280	100	170.0	51-L45-33-0280	8.6	51-L45-21-0280	13.4
315	110	184.0	51-L45-33-0315	9.7	51-L45-21-0315	15.0

### PVDF 45° ELBOW

(Fabricated)  
for butt welding  
molded from PVDF

手工對接45°彎頭  
DFP L47



OD (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	SDR33 ISO S16 PN10		SDR21 ISO S10 PN16	
					Code	S (mm)	Code	S (mm)
355	160	230	302	320	51-L47-33-0355	10.9	-	-
400	180	259	340	360	51-L47-33-0400	12.3	-	-
450	200	289	398	401	51-L47-33-0450	13.7	-	-
500	220	320	410	443	51-L47-33-0500	15.2	-	-
560	240	352	452	485	51-L47-33-0560	17.0	-	-
630	250	375	488	516	51-L47-33-0630	19.1	-	-

手工製品(Fabricated)