




PVDF/PVDF(FRP COATED) PIPE FITTING VALVE

PVDF REDUCER

concentric, elongated
for butt welding
molded from PVDF

對接大小頭
DFP RC1



OD1/OD2 (mm)	L (mm)	L1 (mm)	L2 (mm)	SDR33 ISO S16 PN10		SDR21 ISO S10 PN16	
				Code	S1/S2 (mm)	Code	S1/S2 (mm)
25-20	50	20	20	-	-	51-RC1-21-025020	1.9/1.9
32-20	50	20	20	-	-	51-RC1-21-032020	2.4/1.9
32-25	50	20	20	-	-	51-RC1-21-032025	2.4/1.9
40-20	55	20	20	-	-	51-RC1-21-040020	2.4/1.9
40-25	55	20	20	-	-	51-RC1-21-040025	2.4/1.9
40-32	55	20	20	-	-	51-RC1-21-040032	2.4/2.4
50-20	60	24	20	-	-	51-RC1-21-050020	3.0/1.9
50-25	60	24	20	-	-	51-RC1-21-050025	3.0/1.9
50-32	60	24	20	-	-	51-RC1-21-050032	3.0/2.4
50-40	60	24	20	-	-	51-RC1-21-050040	3.0/2.4
63-25	65	25	20	-	-	51-RC1-21-063025	3.0/1.9
63-32	65	25	22	-	-	51-RC1-21-063032	3.0/2.4
63-40	65	25	22	-	-	51-RC1-21-063040	3.0/2.4
63-50	65	25	22	-	-	51-RC1-21-063050	3.0/3.0
75-40	68	25	24	-	-	51-RC1-21-075040	3.6/2.4
75-50	68	25	24	-	-	51-RC1-21-075050	3.6/3.0
75-63	68	25	24	51-RC1-33-075063	2.3/2.0	51-RC1-21-075063	3.6/3.0
90-50	75	30	26	-	-	51-RC1-21-090050	4.3/3.0
90-63	75	30	26	51-RC1-33-090063	2.8/2.0	51-RC1-21-090063	4.3/3.0
90-75	75	30	26	51-RC1-33-090075	2.8/2.3	51-RC1-21-090075	4.3/3.6
110-63	90	35	30	51-RC1-33-110063	3.4/2.0	51-RC1-21-110063	5.3/3.0
110-75	90	35	30	51-RC1-33-110075	3.4/2.3	51-RC1-21-110075	5.3/3.6
110-90	90	35	30	51-RC1-33-110090	3.4/2.8	51-RC1-21-110090	5.3/4.3
125-110	100	40	35	51-RC1-33-125110	3.9/3.4	51-RC1-21-125110	6.0/5.3
140-125	110	45	40	51-RC1-33-140125	4.3/3.9	51-RC1-21-140125	6.7/6.0
160-110	130	60	40	51-RC1-33-160110	4.9/3.4	51-RC1-21-160110	7.7/5.3
160-140	130	60	40	51-RC1-33-160140	4.9/4.3	51-RC1-21-160140	7.7/6.7
180-160	130	60	40	51-RC1-33-180160	5.5/4.9	51-RC1-21-180160	8.6/7.7
200-160	140	60	40	51-RC1-33-200160	6.2/4.9	51-RC1-21-200160	9.6/7.7
225-160	150	60	40	51-RC1-33-225160	6.9/4.9	51-RC1-21-225160	10.8/7.7
225-200	150	60	50	51-RC1-33-225200	6.9/6.2	51-RC1-21-225200	10.8/9.6
250-225	170	70	60	51-RC1-33-250225	7.7/6.9	51-RC1-21-250225	11.9/10.8
280-250	180	80	60	51-RC1-33-280250	8.6/7.7	51-RC1-21-280250	13.4/11.9
315-280	220	90	80	51-RC1-33-315280	9.7/8.6	51-RC1-21-315280	15.0/13.4



PVDF/PVDF(FRP COATED)

PIPE FITTING VALVE

PVDF REDUCER


(Fabricated)

for butt welding

molded from PVDF

手工對接大小頭

DFP RC1



OD1/OD2 (mm)	L (mm)	L ₁ (mm)	L ₂ (mm)	SDR33 ISO S16 PN10	
				Code	S1/S2 (mm)
355-180	318	180	110	51-RC1-33-355180	10.9/5.5
355-200	328	180	120	51-RC1-33-355200	10.9/6.2
355-225	328	180	120	51-RC1-33-355225	10.9/6.9
355-250	338	180	130	51-RC1-33-355250	10.9/7.7
355-280	358	180	150	51-RC1-33-355280	10.9/8.6
355-315	368	180	160	51-RC1-33-355315	10.9/9.7
400-200	358	210	120	51-RC1-33-400200	12.3/6.2
400-225	358	210	120	51-RC1-33-400225	12.3/6.9
400-250	368	210	130	51-RC1-33-400250	12.3/7.7
400-280	388	210	150	51-RC1-33-400280	12.3/8.6
400-315	398	210	160	51-RC1-33-400315	12.3/9.7
400-355	418	210	180	51-RC1-33-400355	12.3/10.9
450-225	398	250	120	51-RC1-33-450225	13.7/6.9
450-250	408	250	130	51-RC1-33-450250	13.7/7.7
450-280	428	250	150	51-RC1-33-450280	13.7/8.6
450-315	438	250	160	51-RC1-33-450315	13.7/9.7
450-355	458	250	180	51-RC1-33-450355	13.7/10.9
450-400	488	250	210	51-RC1-33-450400	13.7/12.3
500-250	438	280	130	51-RC1-33-500250	15.2/7.7
500-280	458	280	150	51-RC1-33-500280	15.2/8.6
500-315	468	280	160	51-RC1-33-500315	15.2/9.7
500-355	488	280	180	51-RC1-33-500355	15.2/10.9
500-400	518	280	210	51-RC1-33-500400	15.2/12.3
500-450	558	280	250	51-RC1-33-500450	15.2/13.7
560-280	478	300	150	51-RC1-33-560280	17.0/8.6
560-315	488	300	160	51-RC1-33-560315	17.0/9.7
560-355	508	300	180	51-RC1-33-560355	17.0/10.9
560-400	538	300	210	51-RC1-33-560400	17.0/12.3
560-450	578	300	250	51-RC1-33-560450	17.0/13.7
560-500	608	300	280	51-RC1-33-560500	17.0/15.2
630-315	538	350	160	51-RC1-33-630315	19.1/9.7
630-355	558	350	180	51-RC1-33-630355	19.1/10.9
630-400	588	350	210	51-RC1-33-630400	19.1/12.3
630-450	628	350	250	51-RC1-33-630450	19.1/13.7
630-500	658	350	280	51-RC1-33-630500	19.1/15.2
630-560	678	350	300	51-RC1-33-630560	19.1/17.0