



PVDF/PVDF(FRP COATED)


PIPE FITTING VALVE

PVDF 90° ELBOW

for socket welding
molded from PVDF

套接90° 彎頭

DFP L92




OD (mm)	dsp (mm)	t (mm)	k (mm)	L (mm)	SDR 7 PN20	
					Code	Weight (kg/Pc.)
16	24.1	10.0	14.5	24.5	51-L92-07-0016	0.023
20	28.8	14.8	15.5	30.1	51-L92-07-0020	0.038
25	35.0	15.3	17.2	32.5	51-L92-07-0025	0.055
32	42.5	20.75	19.5	40.25	51-L92-07-0032	0.093
40	52.0	25.0	21.2	46.2	51-L92-07-0040	0.146
50	63.7	29.0	24.1	53.1	51-L92-07-0050	0.231
63	80.3	35.0	28.0	63.0	51-L92-07-0063	0.430
75	91.7	39.0	32.4	71.4	51-L92-07-0075	0.552
90	112.0	47.0	37.0	84.3	51-L92-07-0090	1.107
110	132.0	58.0	42.5	100.5	51-L92-07-0110	1.579

PVDF 45° ELBOW

for socket welding
molded from PVDF

套接45° 彎頭

DFP L46



OD (mm)	dsp (mm)	t (mm)	k (mm)	L (mm)	SDR 7 PN20	
					Code	Weight (kg/Pc.)
16	24.1	4.25	14.5	18.75	51-L46-07-0016	0.018
20	29.3	5.20	15.3	20.5	51-L46-07-0020	0.028
25	35.2	6.60	17.2	23.8	51-L46-07-0025	0.043
32	43.0	7.10	19.5	26.6	51-L46-07-0032	0.066
40	52.2	10.0	21.2	31.2	51-L46-07-0040	0.104
50	64.2	10.9	24.1	35.0	51-L46-07-0050	0.168
63	81.0	17.8	28.0	45.8	51-L46-07-0063	0.335
75	91.6	16.1	32.4	48.5	51-L46-07-0075	0.407
90	112.0	21.8	37.0	58.8	51-L46-07-0090	0.520
110	132.0	30.0	42.5	72.5	51-L46-07-0110	0.772