



# HD-PE

# PIPE FITTING VALVE

## HD-PE 80-PIPE

DIN 8074/8075

Storage length: 5m

(Special lengths on request)

直管HD-PE 80

DFF PIO



OD (mm)	Ventilation				SDR41 ISO 520 PN2.5			SDR33 ISO 516 PN3.2			SDR26 ISO 512.5 PN4			内白外黑 黑色厚度 (mm)
	S (mm)	Weight (kg/m)	S (mm)	Weight (kg/m)	Code	S (mm)	Weight (kg/m)	Code	S (mm)	Weight (kg/m)	Code	S (mm)	Weight (kg/m)	
10	-	-	-	-	-	-	-	-	-	-	-	-	-	-
12	-	-	-	-	-	-	-	-	-	-	-	-	-	-
16	-	-	-	-	-	-	-	-	-	-	-	-	-	-
20	-	-	-	-	-	-	-	-	-	-	-	-	-	0.8~1.2
25	-	-	-	-	-	-	-	-	-	-	-	-	-	0.8~1.2
32	-	-	-	-	-	-	-	-	-	-	-	-	-	0.8~1.2
40	-	-	-	-	-	-	-	-	-	-	32-PIO-26-0040	1.8	0.227	1.2~1.8
50	-	-	-	-	-	-	-	32-PIO-33-0050	1.8	0.287	32-PIO-26-0050	2.0	0.314	1.2~1.8
63	-	-	-	-	32-PIO-41-0063	1.8	0.364	32-PIO-33-0063	2.0	0.399	32-PIO-26-0063	2.5	0.494	1.2~1.8
75	-	-	-	-	32-PIO-41-0075	1.9	0.457	32-PIO-33-0075	2.3	0.551	32-PIO-26-0075	2.9	0.675	1.2~1.8
90	-	-	-	-	32-PIO-41-0090	2.2	0.643	32-PIO-33-0090	2.8	0.791	32-PIO-26-0090	3.5	0.978	1.4~2.0
110	-	-	-	-	32-PIO-41-0110	2.7	0.943	32-PIO-33-0110	3.4	1.17	32-PIO-26-0110	4.2	1.43	1.4~2.0
125	-	-	-	-	32-PIO-41-0125	3.1	1.23	32-PIO-33-0125	3.9	1.51	32-PIO-26-0125	4.8	1.84	1.4~2.0
140	-	-	-	-	32-PIO-41-0140	3.5	1.54	32-PIO-33-0140	4.3	1.88	32-PIO-26-0140	5.4	2.32	1.4~2.0
160	-	-	-	-	32-PIO-41-0160	4.0	2.00	32-PIO-33-0160	4.9	2.42	32-PIO-26-0160	6.2	3.04	1.4~2.0
180	-	-	-	-	32-PIO-41-0180	4.4	2.49	32-PIO-33-0180	5.5	3.07	32-PIO-26-0180	6.9	3.79	1.4~2.0
200	-	-	-	-	32-PIO-41-0200	4.9	3.05	32-PIO-33-0200	6.2	3.84	32-PIO-26-0200	7.7	4.69	2.0~3.0
225	-	-	-	-	32-PIO-41-0225	5.5	3.86	32-PIO-33-0225	6.9	4.77	32-PIO-26-0225	8.6	5.89	2.0~3.0
250	-	-	-	-	32-PIO-41-0250	6.2	4.83	32-PIO-33-0250	7.7	5.92	32-PIO-26-0250	9.6	7.30	2.0~3.0
280	-	-	-	-	32-PIO-41-0280	6.9	5.98	32-PIO-33-0280	8.6	7.40	32-PIO-26-0280	10.7	9.10	2.0~3.0
315	-	-	-	-	32-PIO-41-0315	7.7	7.52	32-PIO-33-0315	9.7	9.37	32-PIO-26-0315	12.1	11.6	2.0~3.0
355	-	-	-	-	32-PIO-41-0355	8.7	9.55	32-PIO-33-0355	10.9	11.8	32-PIO-26-0355	13.6	14.6	3.0~4.0
400	8.0	9.9	-	-	32-PIO-41-0400	9.8	12.1	32-PIO-33-0400	12.3	15.1	32-PIO-26-0400	15.3	18.6	3.0~4.0
450	8.0	11.2	-	-	32-PIO-41-0450	11.0	15.3	32-PIO-33-0450	13.8	19.0	32-PIO-26-0450	17.2	23.5	-
500	8.0	11.7	10.0	15.5	32-PIO-41-0500	12.3	19.0	32-PIO-33-0500	15.3	23.4	32-PIO-26-0500	19.1	28.9	-
560	10.0	15.5	-	-	32-PIO-41-0560	13.7	23.6	32-PIO-33-0560	17.2	29.4	32-PIO-26-0560	21.4	36.2	-
630	10.0	19.6	-	-	32-PIO-41-0630	15.4	29.9	32-PIO-33-0630	19.3	37.1	32-PIO-26-0630	24.1	45.9	-
710	12.0	26.4	-	-	32-PIO-41-0710	17.4	38.0	32-PIO-33-0710	21.8	47.2	32-PIO-26-0710	27.2	58.4	-
800	12.0	29.8	-	-	32-PIO-41-0800	19.6	48.1	32-PIO-33-0800	24.5	59.7	32-PIO-26-0800	30.6	73.9	-
900	15.0	42.0	-	-	32-PIO-41-0900	22.0	60.9	32-PIO-33-0900	27.6	75.6	32-PIO-26-0900	34.4	93.4	-
1000	15.0	46.7	-	-	32-PIO-41-1000	24.5	75.2	32-PIO-33-1000	30.6	93.1	32-PIO-26-1000	38.2	115.0	-
1200	18.0	67.1	-	-	32-PIO-41-1200	29.4	108.0	32-PIO-33-1200	36.7	134.0	32-PIO-26-1200	45.9	166.0	-



# HD-PE

# PIPE FITTING VALVE

## HD-PE 80-PIPE

DIN 8074/8075

Storage length:5m

(Special lengths on request)

直管HD-PE 80  
DFP PIO



OD (mm)	Ventilation				SDR17.6 ISO 58.3 PN6			SDR11 ISO 55 PN10			SDR7.4 ISO 53.2 PN16			内径壁厚 (mm)
	S (mm)	Weight (kg/m)	S (mm)	Weight (kg/m)	Code	S (mm)	Weight (kg/m)	Code	S (mm)	Weight (kg/m)	Code	S (mm)	Weight (kg/m)	
10	-	-	-	-	-	-	-	-	-	-	-	-	-	-
12	-	-	-	-	-	-	-	-	-	-	32-PIO-07-0012	1.8	0.060	-
16	-	-	-	-	-	-	-	-	-	-	32-PIO-07-0016	2.2	0.099	-
20	-	-	-	-	-	-	-	32-PIO-11-0020	1.9	0.112	32-PIO-07-0020	2.8	0.154	0.8~1.2
25	-	-	-	-	-	-	-	32-PIO-11-0025	2.3	0.171	32-PIO-07-0025	3.5	0.240	0.8~1.2
32	-	-	-	-	32-PIO-17-0032	1.8	0.179	32-PIO-11-0032	2.9	0.272	32-PIO-07-0032	4.4	0.386	0.8~1.2
40	-	-	-	-	32-PIO-17-0040	2.3	0.285	32-PIO-11-0040	3.7	0.430	32-PIO-07-0040	5.5	0.650	1.2~1.8
50	-	-	-	-	32-PIO-17-0050	2.9	0.440	32-PIO-11-0050	4.6	0.666	32-PIO-07-0050	6.9	0.936	1.2~1.8
63	-	-	-	-	32-PIO-17-0063	3.6	0.688	32-PIO-11-0063	5.8	1.05	32-PIO-07-0063	8.6	1.47	1.2~1.8
75	-	-	-	-	32-PIO-17-0075	4.3	0.978	32-PIO-11-0075	6.8	1.47	32-PIO-07-0075	10.3	2.09	1.2~1.8
90	-	-	-	-	32-PIO-17-0090	5.1	1.39	32-PIO-11-0090	8.2	2.12	32-PIO-07-0090	12.3	3.00	1.4~2.0
110	-	-	-	-	32-PIO-17-0110	6.3	2.08	32-PIO-11-0110	10.0	3.14	32-PIO-07-0110	15.1	4.49	1.4~2.0
125	-	-	-	-	32-PIO-17-0125	7.1	2.66	32-PIO-11-0125	11.4	4.08	32-PIO-07-0125	17.1	5.77	1.4~2.0
140	-	-	-	-	32-PIO-17-0140	8.0	3.34	32-PIO-11-0140	12.7	5.08	32-PIO-07-0140	19.2	7.25	1.4~2.0
160	-	-	-	-	32-PIO-17-0160	9.1	4.35	32-PIO-11-0160	14.6	6.67	32-PIO-07-0160	21.9	9.44	1.4~2.0
180	-	-	-	-	32-PIO-17-0180	10.2	5.48	32-PIO-11-0180	16.4	8.42	32-PIO-07-0180	24.6	11.9	1.4~2.0
200	-	-	-	-	32-PIO-17-0200	11.4	6.79	32-PIO-11-0200	18.2	10.4	32-PIO-07-0200	27.4	14.8	2.0~3.0
225	-	-	-	-	32-PIO-17-0225	12.8	8.55	32-PIO-11-0225	20.5	13.1	32-PIO-07-0225	30.8	18.6	2.0~3.0
250	-	-	-	-	32-PIO-17-0250	14.2	10.6	32-PIO-11-0250	22.7	16.2	32-PIO-07-0250	34.2	23.0	2.0~3.0
280	-	-	-	-	32-PIO-17-0280	15.9	13.2	32-PIO-11-0280	25.4	20.3	32-PIO-07-0280	38.3	28.9	2.0~3.0
315	-	-	-	-	32-PIO-17-0315	17.9	16.7	32-PIO-11-0315	28.6	25.6	32-PIO-07-0315	43.1	36.5	2.0~3.0
355	-	-	-	-	32-PIO-17-0355	20.1	21.2	32-PIO-11-0355	32.2	32.5	32-PIO-07-0355	48.5	46.3	3.0~4.0
400	8.0	9.9	-	-	32-PIO-17-0400	22.7	26.9	32-PIO-11-0400	36.3	41.3	32-PIO-07-0400	54.7	58.8	3.0~4.0
450	8.0	11.2	-	-	32-PIO-17-0450	25.5	34.0	32-PIO-11-0450	40.9	52.3	32-PIO-07-0450	61.5	74.4	-
500	8.0	11.7	10.0	15.5	32-PIO-17-0500	28.4	42.0	32-PIO-11-0500	45.4	64.5	32-PIO-07-0500	68.3	91.8	-
560	10.0	15.5	-	-	32-PIO-17-0560	31.7	52.5	32-PIO-11-0560	50.8	80.8	-	-	-	-
630	10.0	19.6	-	-	32-PIO-17-0630	35.7	66.5	32-PIO-11-0630	57.2	102.0	-	-	-	-
710	12.0	26.4	-	-	32-PIO-17-0710	40.2	84.4	32-PIO-11-0710	64.5	130.0	-	-	-	-
800	12.0	29.8	-	-	32-PIO-17-0800	45.3	107.0	-	-	-	-	-	-	-
900	15.0	42.0	-	-	32-PIO-17-0900	51.0	136.0	-	-	-	-	-	-	-
1000	15.0	46.7	-	-	32-PIO-17-1000	56.7	167.0	-	-	-	-	-	-	-
1200	18.0	67.1	-	-	32-PIO-17-1200	68.0	241.0	-	-	-	-	-	-	-