



# PVC 污水管

## (塑膠管·接頭) PIPE FITTING

### 污水管 (PVC pipe for Sewer)

標稱管徑 Nominal Pipe Size		外徑及 許可差 Outside Diameter and Tolerance	厚度 Wall Thickness		近似內徑 (參考) Approx. Inside Diameter	質量 (參考) Approx. Weight (kg/M)	20°C許可 操作壓力 Allow working Pressure at 20°C(kgf/cm <sup>2</sup> )	長度 Length (M)	code
(mm)	(Inch)		最小 Minimum	許可差 Tolerance					
40	1-1/2"	48±0.4	3.6	+0.8	40	0.795	10	4 M	14-PIO-JS-0040
50	2"	60±0.5	4.1	+0.8	51	1.130	9.0	4 M	14-PIO-JS-0050
65	2-1/2"	76±0.5	4.1	+0.8	67	1.450	8.0	5 M	14-PIO-JS-0065
80	3"	89±0.5	5.1	+0.8	78	2.070	8.0	5 M	14-PIO-JS-0080
90	3-1/2"	100±0.6	5.6	+0.8	88	2.540	8.0	5 M	14-PIO-JS-0090
100	4"	114±0.6	6.6	+1.0	100	3.420	8.0	5 M	14-PIO-JS-0100
125	5"	140±0.8	7.0	+1.0	125	4.490	7.5	5 M	14-PIO-JS-0125
150	6"	165±1.0	8.5	+1.4	148	6.460	7.5	5 M	14-PIO-JS-0150
200	8"	216±1.3	10.5	+1.4	194	10.340	7.5	5 M	14-PIO-JS-0200
250	10"	267±1.6	13.0	+1.8	240	15.860	7.5	5 M	14-PIO-JS-0250
300	12"	318±1.9	15.5	+2.2	286	22.560	7.5	5 M	14-PIO-JS-0300
350	14"	370±2.2	18.0	+2.6	333	30.520	7.5	5 M	14-PIO-JS-0350
400	16"	420±2.6	20.5	+3.0	378	39.480	7.5	5 M	14-PIO-JS-0400
450	18"	470±3.0	22.9	+3.4	423	49.400	7.5	5 M	14-PIO-JS-0450
500	20"	520±3.5	25.3	+3.8	468	60.440	7.5	5 M	14-PIO-JS-0500
600	24"	630±4.0	30.7	+4.0	587	88.070	7.5	5 M	14-PIO-JS-0600

※ 1. 外徑係指任意互相垂直兩外徑之算術平均值。

2. 下水道及建築物污水用管為橘紅色。

※ 1. Average O.D. refers to the arithmetic mean value of any two given O.D. at the right angle to each other.

2. PVC pipes for sewerage and sewer lines are reddish-orange.